



Control Handwheels
Clamping Handles
Rotary Controls
Levelling Elements
Indexing Elements
Level Indicators
Magnets
Joints
Gas Spring
Cylindrical Bellows
Telescopic Slides
Machine Elements

PA6479-000

Ergonomic benefit derived from 14 mm thick worker platform comprised of a long wearing top surface laminated onto a resilient microcellular vinyl base for maximum durability and fatigue relief. Diamond plate pattern provides traction while allowing easy twist turns.

Slip resistance R10 according to DIN51130 and BG-rule BGR181. Tested and certified by the National Floor Safety Institute (NFSI). Featured with RedStop™ slip resistant backing to prevent mats from shifting. Available yellow borders along sides comply with OSHA code 1910-144. Bevelled edges on all four sides to minimize risk of tripping. UniFusion™ technology, engineered to resist in the harshest work environments.

Recommended uses:

- Heavy duty - dry industrial environments

Specifications:

- 4.7 mm PVC top surface permanently bonded onto a 9.3 mm resilient backing of microcellular vinyl.
- Overall thickness: 14 mm.
- Weight: 5.5 kg per m
- Fire classification Bfl-S1 tested according to EN 13501-1.
- Coefficient of friction NSF1 certified.
- Free of DOP, free of DMF, free of ozone depleting substances, free of silicone and free of heavy metals.

Colours:

- Grey, Black, Black/yellow

Stock sizes:

- 60 cm x 91 cm
- 91 cm x 150 cm
- 91 cm x 3 m
- 91 cm x 6 m

Full rolls 22.8 m:

- 60 cm, 91 cm, 122 cm and 152 cm widths

Custom lengths:

- 60 cm, 91 cm, 122 cm and 152 cm widths



PRODUCT TESTING



Control Handwheels
Clamping Handles
Rotary Controls
Levelling Elements
Indexing Elements
Level Indicators
Magnets
Joints
Gas Spring
Cylindrical Bellows
Telescopic Slides
Machine Elements



PA6782-000

Top-of-the-line ergonomic experience, made available in custom lengths. Comfort, durability, and safety are united in this product, designed for those who are not willing to compromise in any of these criteria. Combination of extra hard wearing top surface and a very resilient microcellular vinyl base for maximum fatigue relief.

Ergonomic benefit derived from unique bubble design coupled with 19 mm thick worker platform. Favours slip resistance and freedom of movement; tested R9 according to DIN51130 and BG-rule BGR181. Featured with RedStop™ slip resistant backing to prevent mats from shifting. Available yellow borders along sides comply with OSHA code 1910-144. Bevelled edges on all four sides to minimize risk of tripping. Lifetime warranty on Uni-Fusion™ lamination technology.

Recommended uses:

- Heavy duty - dry industrial environments

Specifications:

- 5 mm of PVC top surface permanently bonded onto a 14 mm resilient backing of microcellular vinyl.
- Overall thickness: 19 mm.
- Weight: 6.9 kg per m².
- Fire classification Cfl-S2 tested according to DIN EN ISO 13501.
- Free of DOP, free of DMF, free of ozone depleting substances, free of silicone and free of heavy metals.

Colours:

- Grey, Black, Black/yellow

Stock sizes:

- 60 cm x 91 cm
- 91 cm x 150 cm
- 91 cm x 2 m
- 91 cm x 3 m
- 91 cm x 6 m

Full rolls 21.9 m:

- 60 cm, 91 cm, 122 cm and 152 cm widths

Custom lengths:

- 60 cm, 91 cm, 122 cm and 152 cm widths

PRODUCT TESTING

